END
DATE
FILMED
3 83
DTIC

MICROCOPY RESOLUTION TEST CHART

NATIONAL BUREAU OF STANDARDS-1963-A

TECHNICAL REPORT RK-CR-82-11

RECENT ADVANCES IN COMBUSTION INSTABILITY ANALYSIS

FOR SOLID PROPELLANT ROCKET MOTORS

T. J. Chung
School of Science and Engineering
The University of Alabama in Huntsville
Huntsville, AL 35899

May 1982

U.S. ARMY MISSILE COMMAND

Redstone Arsenal, Alabama 35809

Approved for public release; distribution unlimited.

83 03 15 063

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER RK-CR-82-11	2. GOVT ACCESSION NO. AD-A125 613	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Recent Advances in Combustion Instability Analysis for Solid Propellant Rocket Motors		5. TYPE OF REPORT & PERIOD COVERED
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) T. J. Chung		8. CONTRACT OR GRANT NUMBER(s) DAAH29-81-D-0100
9. PERFORMING ORGANIZATION NAME AND ADDRESS Commander, US Army Missile Command ATTN: DRSMI-RK Redstone Arsenal, AL 35898		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
11. CONTROLLING OFFICE NAME AND ADDRESS		12. REPORT DATE May 1982
		13. NUMBER OF PAGES 33
14. MONITORING AGENCY NAME & ADDRESS(if different from Controlling Office)		15. SECURITY CLASS. (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE

16. DISTRIBUTION STATEMENT (of this Report)

Cleared for public release; distribution unlimited.

17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)

18. SUPPLEMENTARY NOTES

19. KEY WORDS (Continue on reverse side if necessary and identify by block number)

Vorticity
Coupled Acoustic Instability
Vortex shedding
Velocity Oscillations
Axisymmetric

20. ABSTRACT (Continue on reverse side if necessary and identify by block number)

Three-dimensional combustion stability integrals are derived with effects of viscosity and vorticity incorporated. For clarity of presentation, the particle distributions in gas dynamics are not considered at this time. It is suggested that the finite element method can be utilized to advantage for complicated geometries and boundary conditions. Some of the initial finite element calculations are demonstrated for an illustrative purpose, pending a full scale numerical applications in the future. (Author)

DD FORM 1 JAN 73 1473 EDITION OF 1 NOV 65 IS OBSOLETE

ACKNOWLEDGEMENTS

CONTENTS

1. INTRODUCTION

Factors which contribute to the dissipation of acoustic energy in
the chamber of solid rocket motors during combustion include - nozzle
performance, particulate matter, propellant structural response,
rotational flow, vortex shedding, etc. The most significant effect
appears to be the response of the propellant combustion zone to acoustic
pressure and acoustic velocity oscillations. A large body of literature
exists relative to this subject, the study of which has been pioneered
by Crocco [1], Cantrell and Hart [2], Culick [3,4], and others. Flandro
and Jacobs [5], among others, have noted that vortex shedding can also
lead to an excitation of pressure oscillations in solid propellant
rocket motors. It is also quite possible that high speed mean flows
affect the stability [6] significantly. Effects of transonic flow,
shock waves, fluid viscosity at shear layers, turbulence, nonlinearity
(second order perturbations), and radiation through high temperature
should also be of concern.

The topics of study in this paper are limited to the basic
question of correct stability integral formulation, and to three-
dimensional finite element applications for stability calcuations built
upon the earlier work of Hackett [7]. Because of the flexibility of the
finite element formulations, the present work can be extended, without
difficulty, to a more general case incorporating various effects such
as high speed flow, shock waves, particle and structural damping, turbu-
lence, and radiation.

In what follows we present the formulation which includes con-
sideration of vortex shedding and fluid viscosity. It has been shown
that a simple and special case of the general formulation reduces to

3

the well-known results   such as "flow turning" as well as "velocity

and pressure coupling" terms. Numerical results of some simple geometries

are discussed, pending a full scale computer code development based on the

present formulation.

2. FORMULATION AND GOVERNING EQUATIONS

Consider a compressible, viscous fluid and the corresponding non-

dimensional equations for continuity, momentum, energy, and state, as

follows:

$$\frac{\partial \rho}{\partial t} + \left(\rho u_i\right)_{,i} = 0 \tag{1}$$

$$\rho \frac{\partial u_i}{\partial t} + \rho u_{i,j} u_j + \frac{1}{\gamma} p_{,i} - \frac{1}{Re}\left(u_{i,jj} + \frac{1}{3} u_{j,ji}\right) = 0 \tag{2}$$

$$\rho \frac{\partial T}{\partial t} - \frac{\gamma-1}{\gamma}\frac{\partial p}{\partial t} + \rho T_{,i} u_i - \frac{\gamma-1}{\gamma} p_{,i} u_i + \frac{\gamma(\gamma-1)}{Re}\left(\frac{2}{3} u_{i,i} u_{j,j} - u_{i,j} u_{j,i}\right.$$

$$\left. - u_{j,i} u_{j,i}\right) = 0 \tag{3}$$

$$p = \rho T \tag{4}$$

where the commas denote partial derivatives, the repeated indices imply

summing with the range of index i or j being 3. We use index notation

in preference to vector symbols in order to facilitate clarification in-

volved in integration by parts and computer coding in our later dis-

cussions. The nondimensional quantities are defined as:

4

$$u_i = \frac{\bar{u}_i}{a} \quad , \quad a = \left(\frac{\gamma p_o}{\rho_o}\right)^{\frac{1}{2}}, \quad p = \frac{\bar{p}}{p_o} \quad , \quad T = \frac{C_p(\gamma-1)\bar{T}}{a^2} \quad ,$$

$$x_i = \frac{\bar{x}_i}{L} \quad , \quad t = \frac{a\bar{t}}{L} \quad , \quad Re = \frac{\rho_o a L}{\mu} \quad , \quad \rho = \frac{\bar{\rho}}{\rho_o}$$

The presence of viscous terms is intended for development of shear
layers close to the burning surface although the effect of viscosity
is negligible in the flow domain with high Reynolds numbers.
Substituting Eqs. (1) and (4) into Eq. (3), we obtain

$$\frac{\partial p}{\partial t} + \gamma p u_{i,i} + p_{,i} u_i + \frac{\gamma^2}{Re}\left(\frac{2}{3} u_{i,i} u_{j,j} - u_{i,j} u_{j,i} - u_{j,i} u_{j,i}\right)$$

$$= 0 \tag{5}$$

To obtain the acoustic equation we take the spatial derivative of
Eq. (2) and subtract the results from the time derivative of Eq. (5).

$$\frac{\partial^2 p}{\partial t^2} - \frac{p}{\rho} p_{,ii} = -\frac{\partial}{\partial t}\left(p_{,i} u_i\right) - \gamma \frac{\partial}{\partial t}(p u_{i,i}) + \gamma p\left[\left(u_{i,j} u_j\right)_{,i}\right]$$

$$-\frac{\gamma p}{\rho R_e}\left[u_{i,jji} + \frac{1}{3} u_{j,jii}\right] - \frac{\gamma(\gamma-1)}{Re}\left\{\frac{\partial}{\partial t}\left[\frac{2}{3} u_{i,i} u_{j,j} - u_{i,j} u_{j,i}\right.\right.$$

$$\left.\left. - u_{j,i} u_{j,i}\right]\right\} + \rho_{,i} \frac{\gamma p}{\rho}\left(\frac{\partial u_i}{\partial t} + u_{i,j} u_j\right) \tag{6}$$

At this point we introduce the perturbation expansion to $0\,(\varepsilon)$ for
the velocity u_i, pressure p, and density ρ in the form,

$$u_i = \bar{u}_i + \varepsilon\left(u_i^* + u_i^{'}\right) \tag{7}$$

$$p = 1 + \varepsilon p^{'} \tag{8}$$

$$\rho = 1 + \varepsilon \rho^{'} \tag{9}$$

where the bar, asterisk, and prime denote the mean flow, vortical fluc-
tuation, and acoustic fluctuation, respectively. Expanding Eq. (6) in
terms of the perturbation variables and collecting the $0\,(\varepsilon)$ terms, we

5

arrive at the expression:

$$\frac{\partial^2 p'}{\partial t^2} - p'_{,ii} = -\bar{u}_i \frac{\partial}{\partial t} p'_{,i} - \gamma \frac{\partial p'}{\partial t} \bar{u}_{i,i} + \gamma \left[\bar{u}_{i,j} u_j^* + \bar{u}_{i,j} u_j' \right.$$

$$\left. + u_{i,j}^* \bar{u}_j + u_{i,j}' \bar{u}_j \right]_{,i} - \frac{\gamma}{Re} \left[\left(u_i^* + u_i' \right)_{,jji} + \frac{1}{3} \left(u_j^* + u_j' \right)_{,jii} \right]$$

$$- \frac{2\gamma(\gamma-1)}{Re} \left\{ \frac{\partial}{\partial t} \left[\frac{2}{3} \bar{u}_{i,i} \left(u_j^* + u_j' \right)_{,j} - \bar{u}_{i,j} \left(u_j^* + u_j' \right)_{,i} \right. \right.$$

$$\left. \left. - \bar{u}_{j,i} \left(u_j^* + u_j' \right)_{,i} \right] \right\} \tag{10}$$

Considering the vorticity, defined as,

$$\varepsilon_{ijk} u_{k,j}^* = \xi_i^* \quad , \quad \varepsilon_{ijk} \bar{u}_{k,j} = \bar{\xi}_i \quad , \quad \xi_i = \bar{\xi}_i + \xi_i^* \tag{11}$$

the acoustic equation, Eq. (10), is recast in the form

$$p'_{,ii} - \frac{\partial^2 p'}{\partial t^2} = h \tag{12}$$

where

$$h = \bar{u}_i \frac{\partial p'_{,i}}{\partial t} + \gamma \frac{\partial p'}{\partial t} \bar{u}_{i,i} - \gamma \left[\left(\bar{u}_j u_j^* \right)_{,ii} + \left(\bar{u}_j u_j' \right)_{,ii} - \varepsilon_{ijk} \left(\bar{u}_j \xi_k^* \right. \right.$$

$$\left. \left. + u_j^* \bar{\xi}_k + u_j' \bar{\xi}_k \right)_{,i} \right] + \frac{\gamma}{Re} \left[\left(u_i^* + u_i' \right)_{,jji} + \frac{1}{3} \left(u_j^* + u_j' \right)_{,jii} \right]$$

$$+ \frac{2\gamma(\gamma-1)}{Re} \frac{\partial}{\partial t} \left[\frac{2}{3} \bar{u}_{i,i} \left(u_j^* + u_j' \right)_{,j} - \bar{u}_{i,j} \left(u_j^* + u_j' \right)_{,i} \right.$$

$$\left. - \bar{u}_{j,i} \left(u_j^* + u_j' \right)_{,i} \right] \tag{13}$$

with ε_{ijk} being the permutation symbol. The vorticity transport equation
is obtained by taking a curl of the vector form of Eq. (2), and collect-
ing the terms of $O(\varepsilon)$,

$$\frac{\partial \xi_i^*}{\partial t} - \varepsilon_{ijk} \varepsilon_{kmn} \left[\bar{u}_m \xi_n^* + \left(u_m^* + u_m' \right) \bar{\xi}_n \right]_{,j} - \frac{1}{Re} \xi_{i,jj}^* = 0 \tag{14}$$

Equations (11), (12), and (14) represent the most general

6

vorticity-coupled acoustic problem in which the viscous action of the fluid is fully taken into account. Here the main objective is to determine the growth r a t e given by the stability integral. This subject is discussed in the following section.

3. THE STABILITY INTEGRAL

3.1 Vorticity-Coupled Acoustic Instability

To begin we must first consider the boundary conditions at the burning surface. In the direction normal to the surface, the momentum equation, Eq. (2), takes the form, in terms of $0~(\varepsilon)$,

$$-p'_{,i}~n_i = f \tag{15}$$

with

$$f = \gamma \left\{ \frac{\partial}{\partial t} u'_i + \left(\bar{u}_j~u^*_j \right)_{,i} + \left(\bar{u}_j~u'_j \right)_{,i} - \varepsilon_{ijk} \left(\bar{u}_j~\xi^*_k + u^*_j~\bar{\xi}_k + u'_j~\bar{\xi}_k \right) \right.$$

$$\left. - \frac{1}{Re} \left[\left(u^*_i + u'_i \right)_{,jj} + \frac{1}{3} \left(u^*_j + u'_j \right)_{,ji} \right] \right\} n_i \tag{16}$$

The oscillatory motion of the acoustic media is modeled by

$$p' = \hat{p} e^{ikt} \tag{17a}$$

$$u'_i = \hat{u}'_i e^{ikt} \quad , \quad u^*_i = \hat{u}^*_i e^{ikt} \tag{17b}$$

$$\xi^*_i = \hat{\xi}^*_i e^{ikt} \tag{17c}$$

where k is the complex dimensionless frequency given by

$$k = \omega - i\alpha \tag{18}$$

Here, the imaginary part is known as the growth rate. The instability of acoustic pressure is signified by the growth of α proportional to $e^{\alpha t}$.

Substituting Eq. (17) into Eqs.(12) and (15) yields, respectively,

$$\hat{h} = ik\bar{u}_i \hat{p}_{,i} + ik\gamma\bar{u}_{i,i}\hat{p} - \gamma\left[\left(\bar{u}_j \hat{u}_j^*\right)_{,ii} + \left(\bar{u}_j \hat{u}_j'\right)_{,ii} - \epsilon_{ijk}\left(\bar{u}_j \hat{\xi}_k^* + \hat{u}_j^* \bar{\xi}_k\right.\right.$$

$$\left.\left. + \hat{u}_j' \bar{\xi}_k\right)_{,i}\right] + \frac{\gamma}{Re}\left[\left(\hat{u}_i^* + \hat{u}_i'\right)_{,jji} + \frac{1}{3}\left(\hat{u}_j^* + \hat{u}_j'\right)_{,jii}\right]$$

$$+ \frac{2ik\gamma(\gamma-1)}{Re}\left[\frac{2}{3}\bar{u}_{i,i}\left(\hat{u}_j^* + \hat{u}_j'\right)_{,j} - \bar{u}_{i,j}\left(\hat{u}_j^* + \hat{u}_j'\right)_{,i}\right.$$

$$\left. - \bar{u}_{j,i}\left(\hat{u}_j^* + \hat{u}_j'\right)_{,i}\right] \tag{19}$$

and

$$\hat{f} = \gamma\left\{ik\hat{u}_i' + \left(\bar{u}_j \hat{u}_j^*\right)_{,i} + \left(\bar{u}_j \hat{u}_j'\right)_{,i} - \epsilon_{ijk}\left(\bar{u}_j \hat{\xi}_k^* + \hat{u}_j \bar{\xi}_k\right.\right.$$

$$\left.\left. + \hat{u}_j \bar{\xi}_k\right) - \frac{1}{Re}\left[\left(\hat{u}_i^* + \hat{u}_i'\right)_{,jj} + \frac{1}{3}\left(\hat{u}_j^* + \hat{u}_j'\right)_{,ji}\right]\right\}n_i \tag{20}$$

The foregoing process leads to a nonhomogeneous Helmholtz equation

$$\hat{p}_{,ii} + k^2\hat{p} = \hat{h} \tag{21}$$

subject to the boundary condition

$$\hat{p}_{,i}n_i = -\hat{f} \tag{22}$$

For the solution of Eq. (21) we make use of the Green's function [8]. It can easily be shown that

$$\left(k^2 - k_N^2\right)E_N^2 = \int_\Omega \hat{h}\,\hat{p}_N\,d\Omega + \int_\Gamma \hat{f}\,\hat{p}_N\,d\Gamma \tag{23}$$

where the unperturbed mode shape $\hat{p}_N$ and the wave number k_N are determined from the classical acoustic problem,

$$\hat{p}_{N,ii} + k^2\hat{p}_N = 0 \tag{24}$$

$$\hat{p}_{N,i}n_i = 0 \tag{25}$$

Note that E_N^2 is given by the integral

$$E_N^2 = \int_\Omega \hat{p}_N^2\,d\Omega \tag{26}$$

8

It should be noted that a correct integration of the right-hand side of Eq. (23) is the most crucial aspect of the present study. That is, integration by parts must be carried out until all Neumann boundary conditions are brought to the surface. Since $\hat{h}$ in Eq. (19) contains the terms from the momentum equation differentiated once, it is now necessary that they be integrated by parts twice in order to produce the Neumann boundary conditions. For example, consider a single term taken from Eq. (19) substitued in Eq. (23) and integrated by parts:

$$\int_{\Omega} \left(\hat{u}_j \bar{u}_j \right)_{,ii} \hat{P}_N d\Omega = \int_{\Gamma} \left(\hat{u}_j \bar{u}_j \right)_{,i} n_i \hat{P}_N d\Gamma - \int_{\Omega} \left(\hat{u}_j \bar{u}_j \right)_{,i} \hat{P}_{N,i} d\Omega \tag{27a}$$

Integrating by parts now the second term of Eq. (27a) yields

$$-\int_{\Omega} \left(\hat{u}_j \bar{u}_j \right)_{,i} \hat{P}_{N,i} d\Omega = -\int_{\Gamma} \hat{u}_j \bar{u}_j n_i \hat{P}_{N,i} d\Gamma + \int_{\Omega} \hat{u}_j \bar{u}_j \hat{P}_{N,ii} d\Omega \tag{27b}$$

In order to demonstrate the advantage of tensor notations over vector notations in the process of integrations by parts, we consider a following example (eighth term of Eq. (19) substituted in Eq. (23).

$$\int_{\Omega} u_{i,jji} \hat{P}_N d\Omega = \int_{\Gamma} u_{i,jj} n_i \hat{P}_N d\Gamma - \int_{\Omega} u_{i,jj} \hat{P}_{N,i} d\Omega$$

$$= \int_{\Gamma} u_{i,jj} n_i \hat{P}_N d\Gamma - \int_{\Gamma} u_{i,j} n_j \hat{P}_{N,i} d\Gamma + \int_{\Omega} u_{i,j} \hat{P}_{N,ij} d\Omega \tag{28a}$$

If we pursue the above process in vector notations, we will encounter difficulty in obtaining the last term of Eq. (28a). To see this we begin with

$$\int_{\Omega} \nabla \cdot \nabla^2 \underset{\sim}{u} \, \hat{P}_N \, d\Omega = \int_{\Gamma} \underset{\sim}{n} \cdot \nabla^2 \underset{\sim}{u} \, \hat{P}_N d\Gamma - \int_{\Omega} \nabla^2 \underset{\sim}{u} \cdot \nabla \hat{P}_N \, d\Omega$$

$$= \int_{\Gamma} \underset{\sim}{n} \cdot \nabla^2 \underset{\sim}{u} \, \hat{P}_N \, d\Gamma - \int_{\Gamma} (\underset{\sim}{n} \cdot \nabla) \underset{\sim}{u} \cdot \nabla \hat{P}_N \, d\Gamma + \int_{\Omega} (\ ? \ ) \, d\Omega \tag{28b}$$

9

In integrating by parts $\int_\Omega \nabla^2 \underset{\sim}{u} \cdot \nabla \hat{P}_N \, d\Omega$, only the boundary term can be obtained in vector notations. To obtain the domain term, the quantity $\nabla^2 \underset{\sim}{u} \cdot \nabla \hat{P}_N$ must be expanded into individual terms. Other than in special cases such as this, however, the vector notations can be used to perform integration by parts. But care must be exercised to ensure correct product operations.

An evaluation of the rest of the integrals in Eq. (23) leads to

$$\left(k^2 - k_N^2\right)E_N^2 = i\gamma k_N \int_\Gamma \hat{u}_i' \hat{P}_N n_i \, d\Gamma + ik_N(\gamma+1) \int_\Gamma \bar{u}_i \hat{P}_N^2 n_i \, d\Gamma - ik_N \int_\Omega \bar{u}_{i,i} \hat{P}_N^2 \, d\Omega$$

$$-ik_N(2\gamma+1) \int_\Omega \bar{u}_i \hat{P}_N \hat{P}_{N,i} \, d\Omega + \gamma \int_\Gamma \bar{u}_j \left(\hat{u}_j^* + \hat{u}_j'\right) P_{N,i} n_i \, d\Gamma - \gamma \int_\Omega \bar{u}_j \left(\hat{u}_j^* + \hat{u}_j'\right) P_{N,ii} \, d\Omega$$

$$- \gamma \int_\Omega \varepsilon_{ijk} \left(\bar{u}_j \hat{\xi}_k + \hat{u}_j^* \bar{\xi}_k + \hat{u}_j' \bar{\xi}_k\right) P_{N,i} \, d\Omega$$

$$- \frac{\gamma}{Re} \int_\Gamma \left[\left(\hat{u}_i^* + \hat{u}_i'\right)_{,j} \hat{P}_{N,i} n_j + \frac{1}{3} \left(\hat{u}_j^* + \hat{u}_j'\right)_{,j} P_{N,i} n_i\right] d\Gamma$$

$$+ \frac{\gamma}{Re} \int_\Omega \left[\left(\hat{u}_i^* + \hat{u}_i'\right)_{,j} \hat{P}_{N,ij} + \frac{1}{3} \left(\hat{u}_j^* + \hat{u}_j'\right)_{,j} \hat{P}_{N,ii}\right] d\Omega$$

$$+ \frac{2ik\gamma(\gamma-1)}{Re} \int_\Omega \left[\frac{2}{3} \bar{u}_{i,i}\left(\hat{u}_j^* + \hat{u}_j'\right)_{,j} - \bar{u}_{i,j} \left(\hat{u}_j^* \pm \hat{u}_j'\right)_{,i}\right.$$

$$\left. - \bar{u}_{j,i} \left(\bar{u}_j^* + \hat{u}_j'\right)_{,i}\right] \hat{P}_N \, d\Omega \tag{29}$$

Note that, in view of our choice made in Eq. (25), we set $\hat{p} = \hat{P}_N$ and $k = k_N$ in Eqs. (19) and (20). Squaring both sides of Eq. (18) and in view of $\omega = \omega_N = k_N$ at $\alpha = 0$ for neutral stability, we obtain

$$k^2 - k_N^2 = - i2\alpha k_N + \alpha^2 \tag{30}$$

Comparing Eq. (30) with Eq. (29), we may solve for the growth rate α $(\alpha^2 << |2\alpha K_N|)$ by equating the imaginary parts,

$$\alpha = -\frac{1}{2E_N^2}\Bigg[\int_\Gamma \Bigg\{ \underbrace{\gamma \hat{u}_i^{\prime(R)} \hat{p}_N n_i + (\gamma+1) \bar{u}_i \hat{p}_N^2 n_i}_{(A)} + \underbrace{\frac{\gamma}{k_N} \bar{u}_j \left(\hat{u}_j^* + \hat{u}_j^{\prime}\right)^{(I)} \hat{p}_{N,i} n_i}_{(B)}$$

$$- \underbrace{\frac{\gamma}{k_N Re}\left[\left(\hat{u}_i^* + \hat{u}_i^{\prime}\right)_{,j}^{(I)} \hat{p}_{N,i} n_j + \frac{1}{3}\left(\hat{u}_j^* + \hat{u}_j^{\prime}\right)_{,j}^{(I)} \hat{p}_{N,i} n_i\right]}_{(C)} \Bigg\} d\Gamma$$

$$+ \int_\Omega \Bigg\{ \underbrace{- \bar{u}_{i,i} \hat{p}_N^2 - (2\gamma+1) \bar{u}_i \hat{p}_N \hat{p}_{N,i}}_{(D)} - \underbrace{\frac{\gamma}{k_N}\left[\bar{u}_j\left(\hat{u}_j^* + \hat{u}_j^{\prime}\right)^{(I)} \hat{p}_{N,ii}\right.}_{}$$

$$\underbrace{- \varepsilon_{ijk}\left(\bar{u}_j \hat{\xi}_k + \hat{u}_j^* \bar{\xi}_k + \hat{u}_j^{\prime} \bar{\xi}_k\right)^{(I)} \hat{p}_{N,i}\right]}_{(E)}$$

$$+ \underbrace{\frac{\gamma}{k_N Re}\left[\left(\hat{u}_i^* + \hat{u}_i^{\prime}\right)_{,j}^{(I)} \hat{p}_{N,ij} + \frac{1}{3}\left(\hat{u}_j^* + \hat{u}_j^{\prime}\right)_{,j}^{(I)} \hat{p}_{N,ii}\right]}_{(F)}$$

$$+ \frac{2\gamma(\gamma-1)}{Re}\Bigg[\underbrace{\frac{2}{3}\bar{u}_{i,i}\left(\hat{u}_j^* + \hat{u}_j^{\prime}\right)_{,j}^{(R)} - \bar{u}_{i,j}\left(\hat{u}_j^* + \hat{u}_j^{\prime}\right)_{,i}^{(R)}}_{(G)}$$

$$\underbrace{- \bar{u}_{j,i}\left(\bar{u}_j^* + \hat{u}_j^{\prime}\right)_{,i}^{(R)}\Bigg] \hat{p}_N}_{} \Bigg\} d\Omega \Bigg] \tag{31}$$

where the superscripts (R) and (I) refer to the real and imaginary parts, respectively, and the various terms are defined as:

    (A)   Surface combustion

    (B)   Surface convection

    (C)   Surface viscous damping

    (D)   Combustion into domain

    (E)   Convection into domain

    (F)   Momentum viscous damping

    (G)   Dissipative energy

11

It should be noted that the mean flow vorticity $\bar{\xi}_i$, the vortical

fluctuation $\hat{\xi}_i$, and the vortical component of the velocity $\hat{u}_i^*$ must be

known in order to evaluate the integral, which we shall discuss in

Section 3.2. It is possible, however, to evaluate the stability integral

in an alternative form without explicit values of the vorticity. To this

end, we proceed with the convective term $(\underset{\sim}{u} \cdot \nabla)\underset{\sim}{u}$ instead of $\nabla(\frac{1}{2}u^2) - \underset{\sim}{u} \times \underset{\sim}{\xi}$.

Thus we return to Eq. (23) and examine the integral of the form

$$\int_\Omega \underset{\sim}{\nabla} \cdot (\underset{\sim}{u} \cdot \underset{\sim}{\nabla})\, \underset{\sim}{u}\, \hat{p}_N d\Omega = \int_\Omega \left(u_{i,j}\, u_j\right)_{,i} \hat{p}_N d\Omega \qquad (32)$$

Integrating Eq. (32) by parts twice, we obtain the growth rate similar

to Eq. (31) except that the terms designated as (B) and (E) are replaced

by

$$\alpha_{(B)} = -\frac{1}{2E_N^2} \int_\Gamma \frac{\gamma}{k_N} \left[\bar{u}_i\left(\hat{u}_j^* + \hat{u}_j'\right)^{(I)} + \left(\hat{u}_i^* + \hat{u}_i'\right)^{(I)} \bar{u}_j \right] \hat{p}_{N,i} n_j d\Gamma \quad (33a)$$

$$\alpha_{(E)} = -\frac{1}{2E_N^2} \int_\Omega -\frac{\gamma}{k_N} \left\{\left[\bar{u}_i\left(\hat{u}_j^* + \hat{u}_j'\right)_{,j}^{(I)} + \left(\hat{u}_i^* + \hat{u}_i'\right)^{(I)} \bar{u}_{j,j} \right] \hat{p}_{N,i}\right.$$

$$\left. + \left[\bar{u}_i\left(\hat{u}_j^* + \hat{u}_j'\right)^{(I)} + \left(\hat{u}_i^* + \hat{u}_i'\right)^{(I)} \bar{u}_j \right] \hat{p}_{N,ij}\right\} d\Omega \quad (33b)$$

A careful examination of the integrals above is in order. Recall that the

counterparts of $\alpha_{(B)}$ and $\alpha_{(E)}$ in Eq. (31) were obtained from

$$\int_\Omega \nabla \cdot [\nabla(\frac{1}{2}u^2) - \underset{\sim}{u} \times \underset{\sim}{\xi}]\ \hat{p}_N d\Omega = \int_\Omega \left[\left(u_j u_j\right)_{,ii} - \epsilon_{ijk}\xi_{k,ji} \right] \hat{p}_N d\Omega \qquad (34)$$

The vorticity can be easily removed from Eq. (34) by setting $\underset{\sim}{\xi} = 0$. This can

not be done in the case of Eq. (32). The vortical component $\underset{\sim}{\hat{u}}^*$ can be set equal

to zero in both Eqs. (32) and (34) with $\underset{\sim}{\xi} = 0$ in Eq. (34), but this will not

make both equations equivalent. In other words, the effect of irrotationality cannot be assured from Eq. (32) simply by setting $\hat{u}^* = 0$, and we are aware that

$$[(\bar{\underset{\sim}{u}} + \varepsilon\hat{\underset{\sim}{u}}') \cdot \underset{\sim}{\nabla}](\bar{\underset{\sim}{u}} + \varepsilon\hat{\underset{\sim}{u}}') \neq \underset{\sim}{\nabla}[\frac{1}{2}(\bar{\underset{\sim}{u}} + \varepsilon\hat{\underset{\sim}{u}}') \cdot (\bar{\underset{\sim}{u}} + \varepsilon\hat{\underset{\sim}{u}}')]$$

If the viscous effect is neglected, then the terms designated by (C), (F), and (G) will be eliminated. Thus

$$\alpha = -\frac{1}{2E_N^2}\left[(A) + (B) + (D) + (E)\right] \tag{35}$$

Evaluation of the integrals given by Eqs. (31) and (35) requires adequate analytical or numerical models for the mean flow and vortical and acoustic components of the velocity. These topics will be discussed in Section 5.

If we assume $\xi_i = 0$, $\hat{u}_i^* = 0$, and $\text{Re} \to \infty$ in Eq. (31), we obtain

$$(\alpha_a)_{\xi_i=0} = -\frac{1}{2E_N^2}\left[\int_\Gamma\left[\gamma\,\hat{u}_i^{'(R)}\hat{P}_N\,n_i + (\gamma+1)\,\bar{u}_i\hat{P}_N^2 n_i\right.\right.$$
$$\left.+ \frac{\gamma}{k_N}\bar{u}_j\,\hat{u}_j^{'(I)}\,\hat{P}_{N,i}\,n_i\right]d\Gamma + \int_\Omega\left[-\bar{u}_{i,i}\,\hat{P}_N^2 - (2\gamma+1)\,\bar{u}_i\,\hat{P}_N\hat{P}_{N,i}\right.$$
$$\left.\left.- \frac{\gamma}{k_N}\bar{u}_j\hat{u}_j^{'(I)}\,\hat{P}_{N,ii}\right]d\Omega\right] \tag{36}$$

Here the velocity normal to the boundary surface is expressed in terms of the admittance, $A = A^{(R)} + iA^{(I)}$, and the mean flow Mach number $\bar{M}$ such that

$$\hat{u}_i'n_i = \left(\hat{u}_i^{'(R)} + i\,\hat{u}_i^{'(I)}\right)n_i = \bar{M}\,A\,\hat{P}_N/\gamma \tag{37}$$

whereas the acoustic fluctuation velocity in the domain is given by

$$\hat{u}_i' = \frac{i}{k_N\gamma}\,\hat{P}_{N,i} \tag{38}$$

13

Invoking the relationships of Eqs. (24) and (25) and setting $\bar{u}_{i,i} = 0$ (incompressible flow), one obtains

$$(\alpha_a)_{\xi_{i=0}} = - \frac{1}{2E_N^2} \int_\Gamma \left[\gamma \hat{u}_i^{'(R)} n_i \hat{P}_N + \bar{u}_i \hat{P}_N^2 n_i \right] d\Gamma \qquad (39)$$

which is the familiar expression as derived by Culick [see Eq. (2.29) of Ref. 4 neglecting particle distributions]. This is the simplest form representing the possible unstable motions in a solid propellant rocket motor. It has the ingredients such as velocity coupling (burning rate changes in response to velocity fluctuations parallel to the surface) and pressure coupling (burning rate changes in response to pressure fluctuations on the surface).

Culick, [3,4] further defines the "flow turning" as an averaged approximation to viscous effects which appeared in one-dimensional analysis but did not arise in the three-dimensional inviscid flow. This claim has also been substantiated by the present authors as shown in Eq. (39).

Let us now investigate the terms which result from Eq. (33a,b). The stability integral for the case of $Re \rightarrow \infty$ assumes the form

$$\begin{aligned}
\alpha_a = - \frac{1}{2E_N^2} \Bigg\{ & \int_\Gamma \Bigg[\gamma \hat{u}_i^{'(R)} \hat{P}_N n_i + (\gamma+1) \bar{u}_i \hat{P}_N^2 r_\perp \\
& + \frac{\gamma}{k_N} \left(\bar{u}_i \hat{u}_j^{'(I)} + \hat{u}_i^{'(I)} \bar{u}_j \right) \hat{P}_{N,i} n_j \Bigg] d\Gamma \\
& + \int_\Omega \Bigg[- \bar{u}_{i,i} \hat{P}_N^2 - (2\gamma+1) \bar{u}_i \hat{P}_N \hat{P}_{N,i} - \frac{\gamma}{k_N} \left(\bar{u}_i \hat{u}_{j,j}^{'(I)} + \hat{u}_i^{'(I)} \bar{u}_{j,j} \right) \hat{P}_{N,i} \\
& + \left(\bar{u}_i \hat{u}_j^{'(I)} + \hat{u}_i^{'(I)} \bar{u}_j \right) \hat{P}_{N,ij} \Bigg] d\Omega \Bigg\}
\end{aligned} \qquad (40)$$

14

Now, using the relation given by Eq. (38), we have

$$
\alpha_a = -\frac{1}{2E_N^2}\Bigg\{\int_\Gamma \Bigg[\gamma \hat{u}_i^{\prime(R)}\hat{p}_N\, n_i + (\gamma+1)\,\bar{u}_i\,\hat{p}_N^2\, n_i
$$

$$
+\frac{1}{k_N^2}\,(\bar{u}_i\, P_{N,j}P_{N,i} + \bar{u}_j\, P_{N,i}P_{N,i})\, n_j\Bigg]\,d\Gamma
$$

$$
+\int_\Omega \Bigg[-\bar{u}_{i,i}\hat{p}_N^2 - (2\gamma+1)\,\bar{u}_i\hat{p}_N\hat{p}_{N,i} - \frac{1}{k_N^2}\Big(\bar{u}_i\,\hat{p}_{N,jj}\,\hat{p}_{N,i}
$$

$$
+\bar{u}_{j,j}\,\hat{p}_{N,i}\hat{p}_{N,i} + \bar{u}_i\,\hat{p}_{N,j}\hat{p}_{N,ij} + \bar{u}_j\,\hat{p}_{N,i}\hat{p}_{N,ij}\Big)\Bigg]\,d\Omega\Bigg\} \qquad (41)
$$

For $\bar{u}_{i,i} = 0$, and using Eqs. (24) and (25), we obtain

$$
\alpha_a = -\frac{1}{2E_N^2}\Bigg[\ \int_\Gamma \Big(\underbrace{\gamma\hat{u}_i^{\prime(R)}n_i\hat{p}_N}_{(A\text{-}1)} + \underbrace{\bar{u}_i\,\hat{p}_N^2\, n_i}_{(A\text{-}2)} + \underbrace{\frac{1}{k_N^2}\,\bar{u}_j\hat{p}_{N,i}\hat{p}_{N,i}\, n_j}_{(B)}\Big)\,d\Gamma
$$

$$
+\frac{1}{k_N^2}\int_\Omega \underbrace{(\bar{u}_i\hat{p}_{N,j}\hat{p}_{N,ij} + \bar{u}_j\hat{p}_{N,i}\hat{p}_{N,ij})}_{(D)}\,d\Omega\Bigg] \qquad (42)
$$

According to Culick [3,4], the first two boundary terms are defined as
combustion (at surface) and the last boundary term is known as the mean
flow/acoustic interaction or "flow turning". Note that the "flow turning"
term has appeared from the integration of Eq. (32) by parts "twice". The
boundary term which results from the first integration cancels with a
term from a boundary integral of Eq. (23). Upon integrating by parts
"once more", we obtained the boundary terms in Eq. (33a) which finally led
to the "flow turning" term. Recall that it arises from the convective
term of the momentum equation. The same term, designated as "B" in Eq. (31)
was called "surface convection". Conversely, the domain terms arising from

15

the convective terms of the momentum equation, designated as "D", were called "Convection into domain". These convection terms correspond to the popular definition of the "flow turning" as a consequence of injecting mass into the acoustic wave, which must supply acoustic energy to the mass in order that it be brought up to the local velocity [3,4]. Such action must combine both surface and domain integrals, linking the surface activities into the domain.

3.2 Vorticity Stability Integral

Recall that the coupling of vorticity with an acoustic field given by Eq. (31) is yet to be evaluated from the acceptable velocity profile in the shear layer. The influence of direct acoustic feedback and presence of unstable shear flow are to be taken into account.

One option for the solution is to establish an independent stability integral for vorticity. To this end, we return to Eqs. (14), (17b), and (17c), and write

$$\frac{i}{Re} \hat{\xi}^*_{i,jj} + k\hat{\xi}^*_i = \hat{H}_i \tag{43}$$

where

$$\hat{H}_i = -i \, \varepsilon_{ijk} \varepsilon_{kmn} \left[\bar{u}_m \hat{\xi}^*_n + \left(\hat{u}^*_m + \hat{u}'_m \right) \bar{\xi}_n \right]_{,j} \tag{44}$$

subject to the boundary condition

$$\frac{i}{Re} \hat{\xi}^*_{i,j} \, n_j = -\hat{F}_i$$

16

It is evident that Eq. (43) represents diffusive waves due to production of vortex streets, and that the state of instability is once again determined from the Green's function technique [8]. It can easily be shown that

$$\left(k - k_N\right) D_N^2 = \int_\Omega \hat{H}_i \, \hat{\xi}_i^{*N} d\Omega + \int_\Gamma \hat{F}_i \, \hat{\xi}_i^{*N} d\Gamma \tag{45}$$

where

$$D_N^2 = \int_\Omega \hat{\xi}_i^N \, \hat{\xi}_i^N \, d\Omega = \int_\Omega \varepsilon_{ijk} \, \varepsilon_{i\ell m} \, \hat{u}_{k,j}^{*N} \, \hat{u}_{m,\ell}^{*N} \, d\Omega$$

The unperturbed mode shapes $\hat{\xi}_i^N$ and the wave number k_N are calculated from the homogeneous equations

$$\frac{i}{R_e} \, \hat{\xi}_{i,jj}^{*N} + k \, \hat{\xi}_i^{*N} = 0 \tag{46}$$

$$\hat{\xi}_{i,j}^{*N} \, n_j = 0 \tag{47}$$

The vorticity growth constant α_v can be derived by the relation (18) and (45),

$$\alpha_v = -\frac{1}{D_N^2} \int_\Omega \varepsilon_{ijk} \, \varepsilon_{kmn}\left(\bar{u}_m \hat{\xi}_n^{*N} + \hat{u}_m^{*N} \bar{\xi}_n\right) \hat{\xi}_{i,j}^{*N} d\Omega \tag{48}$$

Note that the term associated with acoustic fluctuation velocity $\hat{u}_k'$ in Eq. (44) drops out as a result of squaring the imaginary number which appears also in Eq. (38), thus making this term a real part. If desired for a computational standpoint, we may replace the vorticity in terms of velocity,

$$\hat{\xi}_i^{*N} = \varepsilon_{ijk} \hat{u}_{k,j}^{*N} , \tag{49a}$$

$$\bar{\xi}_i = \varepsilon_{ijk} \bar{u}_{k,j} \tag{49b}$$

17

Evaluation of Eq. (46) or Eq. (48) is now straightforward once the mean flow $\bar{u}_i$ and fluctuating velocity $\hat{u}_i^{*N}$ or the vorticity ξ_i^{*N} can be numerically determined using the finite element method. The hyperbolic tangent velocity profile for the mean flow and shear layers [9-12] may be used for one-dimensional integration.

The growth rate for the vortex shedding α_v represents an independent vorticity instability equivalent to the solution of Orr-Summerfeld equation. When vortex shedding frequency approximates the classical acoustic frequency, periodic flow separations can produce significant pressure oscillations. To this end we perform the eigenvalue analyses for both Eqs. (24) and (46) and we enter the results into Eq. (31).

4. FINITE ELEMENT ANALYSIS

The use of finite elements in fluid mechanics problems has increased significantly in recent years. An application of this method to combustion instability was first studied in [7]. Our current effort is directed toward extending the work of [7] to incorporate the new terms in the stability integral as described in Section 3.

To begin we return to a classical acoustic problem characterized by Eq. (24) and Eq. (25). The Galerkin finite element equation takes the

form [13],

$$\int_\Omega \left(p_{,ii} + k^2 \, p \right) \Phi_\alpha \; d\Omega = 0 \tag{50}$$

where Φ_α is the test function which is set equal to the trial (basis) function such that

$$p\left(\underset{\sim}{x}, t \right) = \Phi_\alpha \left(\underset{\sim}{x} \right) p_\alpha (t) \tag{51}$$

Here $\underset{\sim}{x}$ and t denote spatial and temporal variations, respectively, the subscript α representing the global node number with $\alpha = 1, 2, - - -, n$, n being the total number of global nodes.

It follows from Eq. (50) that the finite element eigenvalue equation is of the form

$$\left| A_{\alpha\beta} - k^2 \, B_{\alpha\beta} \right| = 0 \tag{52}$$

where

$$A_{\alpha\beta} = \int_\Omega \Phi_{\alpha,i} \, \Phi_{\beta,i} \; d\Omega \quad , \qquad B_{\alpha\beta} = \int_\Omega \Phi_\alpha \, \Phi_\beta \; d\Omega \tag{53}$$

The normal modes $\hat{p}_N$ required for the stability integral can then be determined from Eq. (51). Non-axisymmetric geometries for slots, segments or irregular flow domain are modeled routinely using the Fourier series expansion [7].

Similarly, the vorticity transport Eq. (40) is cast in the form

$$\left| A_{\alpha\beta}^{ik} - k \, B_{\alpha\beta}^{ik} \right| = 0 \tag{54}$$

where

$$A_{\alpha\beta}^{ik} = \frac{i}{Re} \int_\Omega \Phi_{\alpha,j} \Phi_{\beta,j} \delta_{ik} \; d\Omega \quad , \qquad B_{\alpha\beta}^{ik} = \int_\Omega \Phi_\alpha \Phi_\beta \delta_{ik} \; d\Omega \tag{55}$$

The well-known QR algorithm [14] is invoked for the solution of eigenvalues and eigenvectors. As a result, the normal modes $\hat{\xi}_i^{*N}$ or $\hat{u}_i^{*N}$ are calculated and substituted into the stability integrals, Eq. (31) and Eq. (48).

19

Once the normal modes are determined either numerically or anlaytically, the evaluation of stability integrals by finite elements is most appealing. Highly nonlinear, complicated functions can be integrated quite accurately via Gaussian quadrature, using the iso-parametric finite elements [13].

For example, the stability integral is written in the form

$$\alpha = \int_{\Omega} F(\underset{\sim}{x}) \, d\Omega = \int_{-1}^{1} \int_{-1}^{1} \int_{-1}^{1} G(\xi, \eta, \zeta) \, d\xi \, d\eta \, d\zeta \qquad (56)$$

This leads to the Gaussian quadrature process,

$$\alpha = \sum_{i=1}^{m} \sum_{j=1}^{m} \sum_{k=1}^{m} w_i w_j w_k \, G(\xi_i, \eta_j, \zeta_k) \qquad (57)$$

where the weighting functions w_i, w_j, w_k and abscissae ξ_i, η_j, ζ_k are chosen for an adequate number of Gaussian points.

5. APPLICATIONS

5.1 General

The stability integrals given in Section 3 and the finite element equations as shown in Eq. (57) will be discussed. We begin with boundary conditions defined on the burning surface (Γ_b) and the nozzle entrance (Γ_n) as represented by the admittance functions:

$$A_b = -\frac{u_i' n_i}{\bar{M}_b \, p'/\gamma} \qquad \text{on } \Gamma_b \qquad (58)$$

$$A_n = \frac{u_i' n_i}{\bar{M}_n \, p'/\gamma} \qquad \text{on } \Gamma_n \qquad (59)$$

20

where $\bar{M}_b$ and $\bar{M}_n$ are the mean flow Mach numbers on Γ_b and Γ_n, respectively.

At this point, it is important to realize that the different forms of convective terms in the momentum equation would give different results for combustion instability phenomena,

Case 1: $\quad \nabla\left(\frac{1}{2}\,u^2\right) - \underset{\sim}{u} \times \underset{\sim}{\xi}$ $\hfill (60)$

Case 2: $\quad \left(\underset{\sim}{u}\cdot\underset{\sim}{\nabla}\right)\underset{\sim}{u}$ $\hfill (61)$

The difference is particularly significant when dominated by vortex sheddings. To see this, we rewrite Eq. (23) in terms of admittance functions for the Cases 1 and 2, respectively,

Case 1:

$$\alpha = \alpha_a + \alpha_H \hfill (62)$$

where

$$\alpha_a = -\frac{1}{2E_N^2}\left[-A_b^{(R)}\bar{M}_b\int_{\Gamma_b}\hat{P}_N^2 d\Gamma_b + A_n^{(R)}\bar{M}_n\int_{\Gamma_n}\hat{P}_N^2\,d\Gamma_n + \frac{1}{k_N^2}\int_\Gamma \bar{u}_j\hat{P}_{N,j}\hat{P}_{N,i}n_i d\Gamma\right.$$

$$+ (\gamma+1)\int_\Gamma \bar{u}_i\hat{P}_N^2\,n_i\,d\Gamma - \frac{1}{k_N^2 Re}\int_\Gamma\left(\hat{P}_{N,i}\hat{P}_{N,ij}\,n_j + \frac{1}{3}\hat{P}_{N,i}\hat{P}_{N,jj}n_i\right)d\Gamma$$

$$+ \int_\Omega\left\{-\bar{u}_{i,i}\hat{P}_N^2 - (2\gamma+1)\bar{u}_i\hat{P}_N\hat{P}_{N,i} - \frac{1}{k_N^2}\left[\bar{u}_j\hat{P}_{N,j}\hat{P}_{N,ii}\right.\right.$$

$$\left.\left.\left. + \epsilon_{ijk}\bar{\xi}_k\hat{P}_{N,i}\hat{P}_{N,j}\right] + \frac{1}{k_N^2 Re}\left(\hat{P}_{N,ij}\hat{P}_{N,ij} + \frac{1}{3}\hat{P}_{N,ii}\hat{P}_{N,jj}\right)\right\}d\Omega\right]$$

$$\hfill (63a)$$

$$\alpha_H = -\frac{1}{2E_N^2}\left[\int_\Gamma\left\{\frac{\gamma}{k_N}\bar{u}_j\hat{u}_j^{*(I)}\hat{P}_{N,i}n_i - \frac{\gamma}{k_N Re}\left(\hat{u}_{i,j}^*\hat{P}_{N,i}n_j + \frac{1}{3}\hat{u}_{j,j}^{*(I)}\hat{P}_{N,i}n_i\right)\right\}d\Gamma\right.$$

$$+ \int_\Omega\left\{-\frac{\gamma}{k_N}\left[\bar{u}_j\hat{u}_j^{*(I)}\hat{P}_{N,ii} + \epsilon_{ijk}\left(\bar{u}_j\hat{\xi}_k^{(I)} + \hat{u}_j^{*(I)}\bar{\xi}_k\right)\hat{P}_{N,i}\right]\right.$$

$$+ \frac{\gamma}{k_N Re}\left(\hat{u}_{i,j}^{*(I)}\hat{P}_{N,ij} + \frac{1}{3}\hat{u}_{j,j}^{*(I)}\hat{P}_{N,ii}\right)\frac{2\gamma(\gamma-1)}{Re}\left(\frac{2}{3}\bar{u}_{i,i}\hat{u}_{j,j}^{*(R)}\right.$$

$$\left.\left.\left. - \bar{u}_{i,j}\hat{u}_{j,i}^{*(R)} - \bar{u}_{j,i}\hat{u}_{j,i}^{*(R)}\right)\hat{P}_N\right\}d\Omega\right]$$

$$\hfill (63b)$$

Case 2:

$$\alpha_a = -\frac{1}{2E_N^2}\left[-A_b^{(R)}\,\bar{M}_b \int_{\Gamma_b} \hat{p}_N^2\;d\Gamma_b + A_n^{(R)}\,\bar{M}_n \int_{\Gamma_n} \hat{p}_n^2\;d\Gamma_n \right.$$

$$\underbrace{\phantom{-A_b^{(R)}\bar{M}_b \int \hat{p}_N^2}}_{(A-1)}$$

$$\underbrace{-(\gamma+1)\int_\Gamma \bar{u}_i\hat{p}_N^2\,n_i\;d\Gamma}_{(A-2)} + \frac{1}{k_N^2}\int_\Gamma \Big(\underbrace{\bar{u}_j\hat{p}_{N,i}\,\hat{p}_{N,i}\,n_j}_{(B-1)} + \underbrace{\bar{u}_i\hat{p}_{N,i}\,\hat{p}_{N,j}\,n_j}_{(B-2)}\Big)\;d\Gamma$$

$$\underbrace{-\frac{1}{k_N^2 Re}\int_\Gamma \Big(\hat{p}_{N,i}\,\hat{p}_{N,ij}\,n_j + \frac{1}{3}\hat{p}_{N,jj}\,\hat{p}_{N,i}\,n_i\Big)\,d\Gamma}_{(C)} + \int_\Omega\Big\{\underbrace{-\bar{u}_{i,i}\,\hat{p}_N^2}_{(D-1)} \underbrace{-(2\gamma+1)\,\bar{u}_i\,\hat{p}_N\,\hat{p}_{N,i}}_{(D-2)}$$

$$-\frac{1}{k_N^2}\Big(\underbrace{\bar{u}_i\,\hat{p}_{N,jj}\,\hat{p}_{N,i}}_{(E-1)} + \underbrace{\bar{u}_{j,j}\,\hat{p}_{N,i}\,\hat{p}_{N,i}}_{(E-2)} + \underbrace{\bar{u}_i\,\hat{p}_{N,j}\,\hat{p}_{N,ij}}_{(E-3)}$$

$$\left. + \underbrace{\bar{u}_j\,\hat{p}_{N,i}\,\hat{p}_{N,ij}}_{(E-4)}\Big) + \underbrace{\frac{1}{k_N^2 Re}\Big(\hat{p}_{N,ij}\,\hat{p}_{N,ij} + \frac{1}{3}\hat{p}_{N,ii}\,\hat{p}_{N,jj}\Big)}_{(F-1)}\Big\}\;d\Omega\right] \qquad (64a)$$

$$\alpha_H = -\frac{1}{2E_N^2}\left\{\int_\Gamma\Big\{\frac{\gamma}{k_N}\big[\bar{u}_i\hat{u}_j^{*(I)} + \hat{u}^{*(I)}\bar{u}_j\big]\hat{p}_{N,i} - \frac{\gamma}{k_N Re}\big[\hat{u}_{i,j}^{*}\hat{p}_{N,i}n_j\right.$$

$$+ \frac{1}{3}\big(\hat{u}_{j,j}^{*}\hat{p}_{N,i}n_i\big)\big]\Big\}\;d\Gamma + \int_\Omega\Big\{-\frac{\gamma}{k_N}\Big(\bar{u}_i\,\hat{u}_{j,j}^{*(I)}\,\hat{p}_{N,i} + \bar{u}_{j,j}\,\hat{u}_i^{*(I)}\hat{p}_{N,i}$$

$$+ \bar{u}_i\,\hat{u}_j^{*(I)}\hat{p}_{N,ij} + \bar{u}_j\,\hat{u}_i^{*(I)}\,\hat{p}_{N,ij}\Big) + \frac{\gamma}{k_N Re}\Big(\hat{u}_{i,j}^{*(I)}\hat{p}_{N,ij}$$

$$+ \frac{1}{3}\hat{u}_{j,j}^{*(I)}\,\hat{p}_{N,ii}\Big) + \frac{2\gamma(\gamma-1)}{Re}\Big(\frac{2}{3}\bar{u}_{i,i}\,\hat{u}_{j,j}^{*(R)} - \bar{u}_{i,j}\,\hat{u}_{j,i}^{*(R)}$$

$$\left. - \bar{u}_{j,i}\,\hat{u}_{j,i}^{*(R)}\Big)\,\hat{p}_N\Big\}\;d\Omega\right] \qquad (64b)$$

Here α_H denotes the coupling of vortical velocity fluctuations $\hat{u}_i^{*}$ and the local acoustic pressure $\hat{p}_N$.

22

(a) Conical Shape Grain Geometry

$\bar{u}_z = \frac{1}{2} (1 + \tanh y')$

(b) Vortical Fluctuations Coupled with the Acoustic Field $\hat{p}_N$

Figure 1 A Physical Model of the Problem

5.2 Vorticity-Uncoupled Acoustic Instability

We consider the axisymmetric conical geometry (Figure 1a) with a transitional angle ϕ and a port diameter D which diverges into 2D at the nozzle entrance, the transition beginning at $z = L/3$. It is assumed that $a\bar{M}_b = 10$ in/sec, $\gamma = 1.2$, and $\nu = 0.1$ in^2/sec. It is further assumed that the mean flow velocity is given by [16],

$$\bar{u}_i = \bar{M}_b \left[-\frac{R}{r} \sin\left(\frac{\pi r^2}{2R^2}\right) \hat{e}_r + \frac{\pi z}{R} \cos\left(\frac{\pi r^2}{2R^2}\right) \hat{e}_z \right] \qquad (65)$$

where R is the radius as a function of z and $\hat{e}_r$ and $\hat{e}_z$ are unit vectors in the radial and axial directions, respectively.

The classical acoustic modes $\hat{p}_N$ are given by the formulas

$$\hat{p}_N = \cos(k_\ell z) \cos(m\theta) J_m\left(k_{mn} r\right) \qquad (66)$$

with

$$k_N^2 = k_\ell^2 + k_{mn}^2 \qquad (67)$$

where $m = 0, 1, 2, ----$, $k_\ell = \ell\pi/L$ with $\ell = 0, 1, 2, ----$, and k_{mn} are the roots of

$$\frac{d}{dr} J_m\left(k_{mn} r\right) = 0 \text{ at } r = R(z)$$

To evaluate α_a in Eq. (64a), the vorticity-uncoupled growth rate, we make use of Eqs. (65-67), rewrite Eq. (64a) in terms of finite elements, and transform the integrand into the form of Eq. (57). To demonstrate the accuracy of calculations we choose the results of terms given by (A-2) and (B-1) which are shown in Table 1. Here we used 4 x 4 Gaussian points, $\phi = 0$, $L/D = 1$, $A_b^{(R)} = 1$, $A_n^{(R)} \bar{M}_n/\bar{M}_b = 1$. A comparison with analytical calculations indicates an excellent agreement.

24

Mode	$\alpha_{(A-2)}$		$\alpha_{(B-1)}$	
(ℓmn)	Analytical	Present Study	Analytical	Present Study
(100)	−4.400	−4.400	2.000	2.000
(200)	−4.400	−4.400	2.000	2.000
(010)	−6.253	−6.253	0.849	0.848
(110)	−6.253	−6.253	1.683	1.683

Table 1.   Acoustic Instability Growth Rate − Integrals (A-2) and
(B-1) in Eq. (64a).

Figure 2 shows the acoustic instability growth rate α_a versus the

transition angle ϕ for several modes. It is interesting to note that,

for both Case 1 and Case 2, the tangential mode tends to be more unstable in

comparison with other modes, and that instability increases with larger

transition angles. However, for a given mode, Case 1 exhibits more in-

stability than Case 2. To the best of our knowledge this has not been

brought to the attention of the combustion community [17]. Furthermore,

it has been demonstrated in Table 2 that the effect of viscosity (C+F)

is negligible in the cylinder of uniform diameter (no flow separation).

It should be noted that an alternative approach is to perform the

eigenvalue analysis for Eq. (52). The acoustic modes $\hat{p}_N$ are then cal-

culated and used in the evaluation of stability integral. For irregular

geometries (non-axisymmetric) such as occur in the star-shaped pro-

pellants we must resort to the eigenvalue analysis. Numerical results

using the procedure as employed in [7] are forthcoming in a subsequent

paper.

Integrals Mode (ℓmn)		A	B	C	D	E	F
(001)	Case 1	-.0762	0.0	-.0000	.6793	- .1998	-.0421
	Case 2	-.0762	-3.7400	-.0000	.6793	- .5994	-.0421
(010)	Case 1	5.3288	0.0	0.0024	-2.3040	0.6777	-.1102
	Case 2	5.3288	0.0	0.0024	-2.3040	-1.953	-.1102
(100)	Case 1	-7.0292	0.0	0.0061	6.4790	-1.9060	-.0221
	Case 2	-7.0292	2.9130	0.0061	6.4790	-7.561	-.0221
(110)	Case 1	-1.4362	0.0	0.0035	2.9720	- .3740	-.1144
	Case 2	-1.4362	-5.0640	0.0035	2.9720	0.3971	-.0225
(200)	Case 1	-4.8580	0.0	0.0060	4.1420	-1.2180	-.0225
	Case 2	-4.8580	2.1220	0.0060	4.1420	-5.060	-.0225

Table 2. Growth Rates for $\frac{L}{D} = 4$, $\phi = \frac{\pi}{4}$, Eq. 64a.

5.3 Vorticity-Coupled Instability

A complete three-dimensional analysis for the vorticity-coupled in-
stability must follow the eigenvalue analysis as required by Eq. (54).
The vortical modes $\hat{\xi}_i^N$ and disturbances $\hat{u}_i^{*N}$ thus calculated may be sub-
stituted into α_H in Eq. (63b) or Eq. (64b). Similar calculations for
Eq. (47) can be carried out for the case of an acoustic-uncoupled
vorticity instability.

In this paper, however, it is our plan not to be involved in the
eigenvalue analysis but to show an analytical approach using the hyper-
bolic tangent velocity profile for a shear layer [10-12]. Here we
assume the stream function ψ^* (r,z,t) representing a single oscillation

26

Figure 2 The Acoustic Growth Rates α_a Vs. Transition Angles for Different Modes, L/D = 4 and $a\bar{M}_b$ = 10 in/sec.

27

of a disturbance to be of the form [9].

$$\psi^* (r,z,t) = \hat{\psi}^* (r,z) \, e^{ikt} \tag{68}$$

where k is the complex dimensionless frequency defined in Eq. (18). We further assume that the disturbance amplitude of the stream function $\hat{\psi}^* (r,z)$ has the same form as in [10]

$$\hat{\psi}^* (r,z) = e^{-\mu y'} \, e^{i\beta z'} \tag{69}$$

where μ and β are real quantities representing the various mode shapes which may depend on the geometry, and y' and z' are the coordinates normalized with respect to the boundary layer thickness θ_o at the separation point ($z' = 0$) and measured from the inflection point as shown in Figure 1a. That is, the disturbance effect of vortex shedding on the acoustic field is assumed to begin at the critical point ($z' = 0$) and vanish downstream before entering the nozzle. Figure 1b shows the disturbance function $\hat{\psi}^{*(R)}$ coupled with the acoustic field $\hat{p}_N$ for a longitudinal mode. The velocity disturbances $\hat{u}_z^*$ and $\hat{u}_r^*$ for an incompressible axisymmetric flow are given by

$$\hat{u}_z^* = \frac{1}{r} \frac{\partial \hat{\psi}^*}{\partial r} \quad , \quad \hat{u}_r^* = - \frac{1}{r} \frac{\partial \hat{\psi}^*}{\partial z} \tag{70}$$

The mean flow representing a hyperbolic tangent velocity profile [10-12] assumes the form

$$\hat{u}_z = \frac{1}{2} (1 + \tanh y') \tag{71}$$

The shear layer thickness θ_o is found experimentally to be a function of

| μ | β | α_H (sec^{-1}) | | α_v (sec^{-1}) |
		$\ell=1,\ m=n=0$	$\ell=2,\ m=n=0$	
0.2	0.2	92.919 105.043	−132.770 −108.990	−6.437
	0.6	30.522 34.493	− 42.930 − 54.611	5.135
	1.0	0.334 2.137	3.198 − 2.869	−0.000
0.6	0.2	85.758 97.814	−125.730 −102.746	−2.059
	0.6	28.168 32.116	− 40.050 − 52.588	14.789
	1.0	0.426 2.315	2.136 − 4.244	−0.000
1.0	0.2	78.260 95.345	−117.662 −160.654	−2.360
	0.6	25.704 31.305	− 38.040 − 51.912	4.025
	1.0	0.465 2.259	1.246 − 4.543	−0.000

Table 3. Growth Rates α_H and α_v, the Upper Numbers are for
Case 1 and the Lower Numbers for Case 2, $\phi = \pi/2$.

Reynolds numbers and the jet diameters,

$$\theta_o = \frac{cD}{\sqrt{Re^{(S)}}} \tag{72}$$

where

$$Re^{(S)} = U_o D/\nu \tag{73}$$

with U_o being the free stream velocity, and $c_o \doteq 0.62$ for cylindrical geometries [12].

For various vortical mode shape combinations of μ and β the growth rates α_H and α_V are calculated for the two first longitudinal modes (Table 3). Here the same physical constants are used as in Figure 1 with $\phi = \pi/2$. Note that α_V is independent of the acoustic mode and $\alpha_H=0$ for any tangential modes. The results indicate that α_H is strongly dependent on β while slightly dependent on μ for the two longitudinal modes, and that the higher mode is more stable than the lower one. Note also that the trend of α_V is similar to that of α_H but α_V has the largest instability occurring at $\beta = 0.6$, and neutral stability at $\beta=1$ for all μ's.

For the first longitudinal mode, the values of α_H are in the range of the case investigated in [9].

6. CONCLUSIONS

A significant improvement over the current practice of combustion stability calculations is achieved. A three-dimensional formulation of stability integral for the coupled acoustic-vortex fluctuations leads to new integral terms accounting for the various phenomena previously neglected.

30

One of the terms in three-dimensional combustion instability integral, identified as "flow-turning", was shown to be the result of integrating by parts, twice, one of the convective terms of the momentum equation. The most crucial factor is the correct procedure for integration by parts which will affect the accuracy in determining the instability. It has been shown that in a three-dimensional case, the use of tensorial approach is more efficient than the vector notations.

The viscosity effect is small as expected for the uniform cylinder. However, it will contribute greatly if the geometry becomes irregular.

A new vortical instability integral is derived, which represents the classical hydrodynamic instability. This avoids solution of the three-dimensional Orr-Summerfeld equation. A simple case of hyperbolic tangent velocity profile is used for shear layer instability calculations. In the case of an acoustic-coupled vortical instability, it is noted that no contribution results from tangential modes.

In this study, we utilize an analytical form of classical normal modes for the cylindrical acoustic field. For irregular geometeries, however, we must resort to the standard eigenvalue analysis to obtain the acoustic and vortical mode shapes and frequencies. With such data we return to the stability integral and proceed identically as shown in the simple examples given in this paper.

References

1. Crocco, L. and Chen, S. I., "Theory of Combustion Instability in Liquid Propellant Rocket Motors," AGARDograph No. 8, Butterworth Scientific Publication, London, 1956.

2. Cantrell, R. H. and Hart, R., "Interaction Between Sound and Flow in Acoustic Cavities: Mass, Momentum, and Energy Considerations," Journal of the Acoustical Society of America, Vol. 36, April, 1964, pp. 697-706.

3. Culick, F. E. C., "The Stability of One-Dimensional Motions in a Rocket Motor," Vol. 7, 1973, pp. 165-175.

4. Culick, F. E. C., "Stability of Three-Dimensional Motions in a Combustion Chamber," Comb. Sci. and Tech., Vol. 10, 1975, pp. 109-124.

5. Flandro, G. A. and Jacobs, H. P., "Vortex Generated Sound in Cavities," Progress in Aeronautics and Astronautics, Vol. 37, AIAA, 1975, pp. 521-533.

6. Flandro, G. A., "Stability Prediction for Solid Propellant Rocket Motors with High Speed Mean Flow," AFRPL-TR-79-98, 1980.

7. Hackett, R. M., "Three-Dimensional Finite-Element Acoustic Analyses of Solid Rocket Motor Cavities," Journal of Space Craft and Rockets, Vol. 13, No. 10, 1976, pp. 585-588.

8. Morse, P. M. and Feshback, H., Methods of Theoretical Physics, Part I and II, McGraw-Hill Book Co., 1953.

9. Brown, R. S., Dunlap, R., Young, S.W., Flandro, G. A., Isaacson, L. K., Beddini, R. A., and Culick, F. E. C., "Vortex Shedding Studies," AFRPL-TR-80-13, April, 1980.

10. Michalke, A., "On Spatially Growing Disturbances in an Inviscid Shear Layer," Journal of Fluid Mechanics, Vol. 23, Part 3, 1965, pp. 521-554.

11. Michalke, A., "On the Inviscid Instability of the Hyperbolic-Tangent Velocity Profile," Journal of Fluid Mechanics, Vol. 19, Part 3, 1964, pp. 543-556.

12. Freymuth, P., "On Transition in a Separated Liminar Boundary Layer," Journal of Fluid Mechanics, Vol. 25, Part 4, 1966, pp. 683-704.

13. Chung, T. J., Finite Element Analyses in Fluid Dynamics, McGraw-Hill Book Co., 1978.

14. Wilkinson, J. H., The Algebraic Eigenvalue Problem, Clarendon Press, Oxford, 1965.

15. Dong, S. B., "A Block-Stodola Eigensolution Technique for Large Algebraic Systems with Nonsymmetrical Matrices," _Int. J. for Numerical Meth. in Eng._, Vol, 1, 11, 1977, pp. 247-267.

16. Culick, F. E. C., "Rotational Axisymmetric Mean Flow and Damping of Acoustic Waves in a Solid Propellant Rocket," _AIAA J._, Vol. 4, No. 8, August, 1966.

17. Lovine, R. L., "Standard Stability Prediction Method for Solid Rocket Motors," AFRPL-TR-76-32, Aerojet Solid Propulsion Co., May, 1976.

DISTRIBUTION

No. of
Copies

Defense Documentation Center
Cameron Station
Alexandria, Virginia 22314   12

IIT Research Institute
ATTN: GACIAC
10 West 35th Street
Chicago, Illinois 60616   1

US Army Material Systems Analysis Activity
ATTN: DRXSY-MP
Aberdeen Proving Ground, Maryland 21005   2

CPIA Distribution   96

Air Force Rocket Propulsion Laboratory
ATTN: DYSC/Mr. W. Roe   1
       Mr. J. Levin   1
Edwards, California 93523

Hercules, Inc.
ATTN: Mr. N. Peterson   1
P. O. Box 98
Magna, Utah 84044

Chemical Systems Division
United Technologies
ATTN: Dr. R. S. Brown   1
       Mr. R. Waugh   1
Sunnyvale, California 94088

California Institute of Technology
ATTN: Dr. F. E. C. Culick   1
204 Karman Laboratory/Mail No. 301-46
1201 East California
Pasadena, California 91109

Naval Weapons Center
Aerothermochemistry Division
ATTN: Code 608, Dr. R. L. Derr   1
                 Mr. B. Matthes   1
                 Mr. C. J. Bicker   1
China Lake, California 93555

DISTRIBUTION

No. of
Copies

California State University
Department of Mechanical Engineering
ATTN: Dr. F. Reardon   1
Sacramento, California 95819

Georgia Institute of Technology
Department of Aerospace Engineering
ATTN: Dr. E. W. Price   1
       Dr. B. T. Zinn   1
Atlanta, Georgia 30332

Rockwell International Corporation
Rocketdyne Division
ATTN: Mr. W. T. Brooks
P. O. Box 548
McGregor, Texas 76657

NASA-Marshall Space Flight Center
ATTN: Mr. B. Shackelford   1
       Mr. C. Forsythe   1
       EP25
Huntsville, Alabama 35812

Aerojet Solid Propulsion Company
ATTN: Mr. R. L. Lovine   1
Building 2019/Department 4350
P. O. Box 13400
Sacramento, California 95813

University of Utah
Department of Mechanical Engineering
ATTN: Dr. G. A. Flandro   1
Salt Lake City, Utah 84112

Thiokol Chemical Corporation
Wasatch Division
ATTN: Dr. C. M. Milfeith   1
       Mr. S. Folkman   1
P. O. Box 524
Brigham City, Utah 94302

Thiokol Chemical Corporation
Huntsville Division
ATTN: Dr. R. Kruse   1
       Mr. R. Hessler   1
       Mr. G. Estes   1
Huntsville, Alabama 35807

DISTRIBUTION

No. of
Copies

Princeton University
Department of Aerospace and Mechanical Science
ATTN: Dr. W. A. Sirignano   1
P. O. Box 710
Princeton, New Jersey 08540

Commander
US Army Materiel and Readiness Command
ATTN: DRCRD   1
       DRCDL   1
5001 Eisenhower Avenue
Alexandria, Virginia 22333

Battelle Columbus Laboratories
Durham Office   1
P. O. Box 8796
Durham, North Carolina 27707

Hercules, Inc.
Allegany Ballistics Laboratory
ATTN: Mr. J. Murray   1
P. O. Box 210
Cumberland, Maryland 21502

DRSMI-FM, Mr. Little   1
DRSMI-LP, Dr. Garvin   1
DRSMI-X   1
DRSMI-R, Dr. McCorkle   1
DRSMI-R, Dr. Rhoades   1
DRSMI-R, Mr. Black   1
DRSMI-RKK   1
DRSMI-RKA   10
DRSMI-RKP   1
DRSMI-RKC   1
DRSMI-RPR   5
DRSMI-IYB   1
DRSMI-RPT (Record Copy)   1
           (Reference Copy)   1

ATE
LME
8